KIN S - SM - B01

Battery Powered Strike with Integrated Access Control

No cutting. No wiring.
No power supply required.



Full Access Control, No Trade-offs

- **Your Phone Is the Key:** Manual or automatic unlocking. No cards, fobs, PINs or readers.
- **Secure by Design:** 256-bit encrypted, time-based credentials, never stored in the lock.
- **Manage From Anywhere:** Users, schedules and audit trails, from phone app or PC.
- **No Infrastructure:** No servers, panels or internet. Unlimited sites and users.

Wire-Free & Built to Last

- **7-Year Battery Life:** Based on 30 unlockings per day (100,000 max).
- **No Wiring:** Powered by 4× CR123 batteries. No power supply needed.
- **No Cutting Required:** Surface mounts on wood and metal frames. Non-handed.
- **Heavy-Duty:** Stainless Steel 304. 1,500 lbs (680 kg) static, 70 ft-lbs (95 J) dynamic.

Frame & Latch	Wood and metal frames, up to ½" (13 mm) throw latchbolt
Power	4× CR123 batteries (not included), in battery pack
Bluetooth® Range	Up to 30 ft (9 m) without obstacles, 2.4 GHz
Temperature Range	32°F to 120°F (0°C to 49°C)
Dimensions	8⅞ × 1¾ × ⅝ in (225 × 44 × 16 mm), L × W × H; ⅛" (3 mm) spacer plate (optional)
Finish	Stainless Steel 304 (strike, battery pack and pad)
Strength	Static 1,500 lbs (680 kg) · Dynamic 70 ft-lbs (95 J) · 250,000 cycles
Battery Pack	1⅝ × 3⅞ × 1 in (41 × 98 × 25 mm), 50°F to 120°F (10°C to 49°C)
Activation Pad	1⅛" (29 mm) diameter, IP65, 0°F to 120°F (−18°C to 49°C)
Certifications	ANSI/BHMA A156.31, Grade 1 · RoHS compliant · UL 1034 burglary-resistant listed
Warranty	3 years

Simple licensing: 2 free users included. Add or transfer user seats anytime in the Kindoo app (iOS® and Android™), monthly or one-time. **Partners** share in user revenue, tracked live in an online portal.

US Patents: US11861960B1, US10325430B2, US12196005 · © 2026 Kindoo. All Rights Reserved.